

QUANTUM 26000 SECURITY GATEWAY



Quantum Security Gateway™ Advantage

Uncompromising Security

Security at Hyperscale

Unified Security

Check Point Quantum 26000 Next Generation Firewalls enables enterprises to deploy the industry's leading threat prevention capabilities at all points of their infrastructure, scaling security almost infinitely according to their changing business needs. It also dramatically accelerates the efficiency of their security operations. This enables enterprises to prevent and block even the most advanced attacks, before they can disrupt business.



Always Protected against Gen V Attacks

Highest caliber prevention
with unified security



Security at Hyperscale

On-demand expansion
with hyperscalability



Efficient Operations

Cut operation management
time by up to 80%


PERFORMANCE HIGHLIGHTS

Gen II Security Firewall	Gen III Security NGFW ¹	Gen V Security Advanced Threat Prevention ²
106.2 Gbps	40.5 Gbps	24 Gbps

Performance measured with enterprise testing conditions. Additional performance details on page 3. 1: Includes Firewall, Application Control, and IPS. 2: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection.

SPOTLIGHT

26000 SECURITY GATEWAY



- | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ol style="list-style-type: none"> 1. RJ45 and USB Type-C console ports 2. Lights-out Management port 3. Sync 10/100/1000 Base-T port 4. ESD grounding point 5. 2x 480GB SSD RAID1 | <ol style="list-style-type: none"> 6. 2x USB 3.0 ports 7. Management 10/100/1000 Base-T port 8. Eight network card expansion slots
3x redundant power supplies (back view not shown)
4x field replaceable fans (back view not shown) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Prevent Known and Zero-day Threats

Check Point SandBlast Threat Emulation is an evasion-resistant sandbox that provides zero-day protection from advanced and unknown threats. SandBlast Threat Extraction (CDR) ensures quick delivery of safe email and web content to users.

	NGFW	NGTP	SNBT
Firewall, VPN, Mobile Access	✓	✓	✓
Content Awareness	✓	✓	✓
Application Control	✓	✓	✓
Intrusion Prevention System	✓	✓	✓
URL Filtering	✓	✓	✓
Antivirus and Anti-Bot	✓	✓	✓
DNS Security	✓	✓	✓
Threat Emulation (sandboxing)	✓	✓	✓
Threat Extraction (CDR)	✓	✓	✓
Zero Phishing	✓	✓	✓

Next Generation Firewall, Next Generation Threat Prevention and SandBlast packages

IoT Security

Quantum IoT Protect now provides autonomous threat prevention. Quantum Firewalls discover IoT assets, feed those to the IoT Cloud Service to automatically map IoT devices to profiles and then apply a zero-trust policy on the firewalls to prevent IoT threats in 5 minutes.

High Performance Options

Purchase the affordable Plus package and get a base system plus twelve 10Gb ports, transceivers, 2x 480 GB SSD drives, Lights-out Management and 96 GB of memory for high connection capacity.



100, 40 and 25 GbE Connectivity

If you're ready to move from 10 to 25, 40 or 100 GbE, so is the 26000 Next Generation Security Gateway. The 26000 Security Gateway lets you connect your 10 GbE server uplinks to your core network.

DATA CENTER GRADE PLATFORM

	1 GbE copper	1 GbE fiber	10 GbE	40 GbE	100/25 GbE	Memory	Redundant Power	Redundant Storage	LOM
Base model	10	0	0	0	0	48 GB	●	○	○
Plus model	10	0	12	0	0	96 GB	●	●	●
Max capacity	66	32	32	16	16	128 GB	●	●	●

○ optional accessory

SPECIFICATIONS

Performance

Enterprise Test Conditions

Threat Prevention ¹ (Gbps)	24
NGFW ² (Gbps)	40.5
IPS (Gbps)	43
Firewall (Gbps)	106.2

RFC 3511, 2544, 2647, 1242 Performance (Lab)

Firewall 1518B UDP (Gbps)	316.5
VPN AES-128 (Gbps)	40.1
Connections/sec	550,000
Concurrent connections ³	10/20/32M ³

1. Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection with logging enabled. 2. Includes Firewall, Application Control and IPS with logging enabled. 3. Performance measured with Base/Plus/maximum memory.

Additional Features

Highlights

- 2x CPUs, 36 physical cores, 72 virtual cores (total)
- 1x 1TB HDD or 480GB SSD, (2x SSD in Plus)
- 3x AC power supplies (DC option)
- 48, 96 and 128 GB memory options
- Lights-Out-Management card (optional in Base package)
- Virtual Systems (base/PLUS/max mem): 125/250/250

Network Expansion Slot Options (7 of 8 slots open)

- 8x 10/100/1000Base-T RJ45 port card, up to 66 ports
- 4x 1000Base-F SFP port card, up to 32 ports
- 4x 10GBase-F SFP+ port card, up to 32 ports
- 2x 40G QSFP+ port card, up to 16 ports
- 2x 100/25G QSFP28 port card, up to 16 ports

Content Security

First Time Prevention Capabilities

- CPU-level, OS-level and static file analysis
- File disarm and reconstruction via Threat Extraction
- Average emulation time for unknown files that require full sandbox evaluation is under 100 seconds
- Maximal file size for Emulation is 100 MB
- Emulation OS Support: Windows XP, 7, 8.1, 10

Applications

- Use 8,500+ pre-defined or customize your own applications
- Accept, prevent, schedule, and apply traffic-shaping

Data Loss Prevention

- Classify 700+ pre-defined data types
- End user and data owner incident handling

Content Security (continued)

Dynamic User-based Policy

- Integrates with Microsoft AD, LDAP, RADIUS, Cisco pxGrid, Terminal Servers and with 3rd parties via a Web API
- Enforce consistent policy for local and remote users on Windows, macOS, Linux, Android and Apple iOS platforms

Network

Network Connectivity

- Total physical and virtual (VLAN) interfaces per appliance: 1024/4096 (single gateway/with virtual systems)
- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

High Availability

- Active/Active L2, Active/Passive L2 and L3
- Session failover for routing change, device and link failure
- ClusterXL or VRRP

IPv6

- NAT66, NAT64, NAT46
- CoreXL, SecureXL, HA with VRRPv3

Unicast and Multicast Routing (see SK98226)

- OSPFv2 and v3, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-SSM, PIM-DM, IGMP v2, and v3

Physical

Power Requirements

- Single Power Supply rating AC: 850W, DC: 1300W
- Power input: 100 to 240V (47-63Hz), 40--72VDC
- Power consumption avg/max: AC330/909W
- Maximum thermal output AC: 3101 BTU/hr.

Dimensions

- Enclosure: 3RU
- Dimensions (WxDxH): 17.4 x 24 x 5.2 in. (442 x 610 x 132mm)
- Weight: 46.3 lbs. (21 kg)

Environmental Conditions

- Operating: 0° to 40°C, humidity 5% to 95%
- Storage: -20° to 70°C, humidity 5% to 95% at 60°C

Certifications

- Safety: UL, CB, CE, TUV GS
 - Emissions: FCC, CE, VCCI, RCM/C-Tick
 - Environmental: RoHS, WEEE, REACH¹, ISO14001¹
- ¹. factory certificate

ORDERING QUANTUM 26000 SECURITY GATEWAYS

SECURITY APPLIANCE ¹	SKU
26000 Base configuration: 10x 1GbE copper ports, 48 GB RAM, 1x 1TB HDD, 3x AC PSUs, telescopic rails, SandBlast (SNBT) Subscription Package for 1 Year, (HDD standalone support).	CPAP-SG26000-SNBT
26000 Plus configuration: 10x 1GbE copper ports, 12x 10GbE SFP+ ports, 12x SR transceivers, 96 GB RAM, 2x 480GB SSD, 3x AC PSUs, LOM, telescopic rails, 5 VS, SandBlast (SNBT) for 1 Year.	CPAP-SG26000-PLUS-SNBT
Quantum IoT Network Protection for 1 year for 26000 appliance	CPSB-IOTP-26000-1Y

The Base package includes 2 trial virtual systems (VS). These are not additive or counted when adding additional VS licenses. Plus includes 5 VS licenses which are additive when adding additional VS licenses.

¹ Renewal NGFW, NGTP and SandBlast (SNBT) packages are available in the online product catalog.

Accessories

INTERFACE CARDS AND TRANSCEIVERS	
8 Port 10/100/1000 Base-T RJ45 interface card	CPAC-8-1C-C
4 Port 1000Base-F SFP interface card; requires additional 1000Base SFP transceivers	CPAC-4-1F-C
SFP transceiver module for 1G fiber ports - long range (1000Base-LX)	CPAC-TR-1LX-C
SFP transceiver module for 1G fiber ports - short range (1000Base-SX)	CPAC-TR-1SX-C
SFP transceiver to 1000 Base-T RJ45 (Copper)	CPAC-TR-1T-C
4 Port 10GBase-F SFP+ interface card	CPAC-4-10F-C
SFP+ transceiver module for 10G fiber ports - for links up to 40km (10GBASE-ER)	CPAC-TR-10ER-C
SFP+ transceiver module for 10G fiber ports - long range up to 10km (10GBase-LR)	CPAC-TR-10LR-C
SFP+ transceiver module for 10G fiber ports - short range (10GBase-SR)	CPAC-TR-10SR-C
SFP+ transceiver 10GBASE-T RJ45 (Copper) - for links up to 30m over CAT6a/CAT7	CPAC-TR-10T-C
10G Direct Attach Copper (DAC) Cable, (10BASE-CU) 3 meters	CPAC-DAC-10G-3M
2 Port 40G QSFP+ interface card	CPAC-2-40F-C
QSFP+ transceiver module for 40G fiber ports - short range (40GBase-SR)	CPAC-TR-40SR-QSFP-300m
QSFP+ transceiver module for 40G fiber ports - long range (40GBase-LR)	CPAC-TR-40LR-QSFP-10Km
40G Direct Attach Copper (DAC) cable, three meters (40BASE-CR4)	CPAC-DAC-40G-3M
Bi-directional QSFP transceiver for 40G fiber Ports - short range (40GBase-SR-BD)	CPAC-TR-40SR-QSFP-BiDi
2 Port 100/25G QSFP28 interface card	CPAC-2-100/25F
QSFP28 transceiver module for 100G fiber ports - short range (100GBase-SR4)	CPAC-TR-100SR
QSFP28 transceiver module for 100G fiber ports - long range (100GBase-LR4)	CPAC-TR-100LR
100G SWDM4, LC connector, 75m/OM3 fiber	CPAC-TR-100SWDM4
100G CWDM4, LC connector, 2Km/ single mode fiber	CPAC-TR-100CWDM4
SFP28 transceiver module for 25G fiber ports with QSFP28 adaptor - short range (25GBase-SR)	CPAC-TR-25SR-ADP
SFP28 transceiver module for 25G fiber ports with QSFP28 adaptor - long range (25GBase-LR)	CPAC-TR-25LR-ADP
100G Direct Attach Copper Cable (QSFP28), 3 meters	CPAC-DAC-100G-3M

FAIL-OPEN NETWORK INTERFACE CARDS	
4 Port 1GE copper Bypass (Fail-Open) Network interface card (10/100/1000 Base-T)	CPAC-4-1C-BP-C
2 Port 10GE Short-range Fiber Bypass (Fail-Open) Network interface card (10GBase-SR)	CPAC-2-10FSR-BP-C

ORDERING 26000 (Continued)

MEMORY	SKU
Memory upgrade kit from 48GB to 96GB for 26000 Security Gateways	CPAC-RAM48GB-26000
Memory upgrade kit from 96GB to 128GB for 26000 Security Gateways	CPAC-RAM32GB-26000
Memory upgrade kit from 48GB to 128GB for 26000 Security Gateways	CPAC-RAM80GB-26000

SPARES AND MISCELLANEOUS	SKU
1TB HDD for 16000/26000 Security Gateways	CPAC-HDD-1T-C
480GB SSD for 16000/26000 Security Gateways	CPAC-SSD-480G-C
AC power supply for 16600HS, 26000, 28000, 28600HS Security Gateways	CPAC-PSU-AC-26000/28000
Dual DC power supplies for 16000 and 26000 Security Gateways	CPAC-PSU-DC-Dual-16000/26000/28000
DC power supply for 16000 and 26000 Security Gateways	CPAC-PSU-DC-16000/26000
Replacement Lights-Out Management Module	CPAC-NLOM-C
Replacement Fan	CPAC-FAN-26000/28000
Slide rails for 26000 Security Gateways (22" - 32")	CPAC-RAIL-L
Extended slide rails for 26000 Security Gateways (24" - 36")	CPAC-RAIL-EXT-L

All-inclusive Security

	NGFW	NGTP	SNBT (SandBlast)
	Basic access control plus IPS	Prevent known threats	Prevent known and zero-day attacks
Firewall	✓	✓	✓
VPN (IPsec)	✓	✓	✓
Application Control	✓	✓	✓
Content Awareness	✓	✓	✓
IPS	✓	✓	✓
URL Filtering		✓	✓
Anti-Bot		✓	✓
Anti-Virus		✓	✓
Anti-Spam		✓	✓
DNS Security		✓	✓
SandBlast Threat Emulation			✓
SandBlast Threat Extraction			✓
Zero Phishing			✓
IoT Network Protection	optional	optional	optional

The first-year purchase includes the SNBT package. Security subscription renewals, NGFW, NGTP and SNBT are available for subsequent years.